- 1. Identification of the substance and of the company
- 2. Hazards Identification
- 3. Composition/Information on ingredients
- 4. First-aid measures
- 5. Fire-fighting measures
- 6. Accidental release measures
- 7. Handling and storage
- 8. Exposure controls/personal protection
- 9. Physical and chemical properties
- 10. Stability and reactivity
- 11. Toxicological information
- 12. Ecological information
- 13. Disposal considerations
- 14. Transport information
- 15. Regulatory information
- 16. Other information

- \* Classification: not hazardous material pursuant to Regulation (EC) no. 1272/2008 EC or EC Directive 67/548/ EEC \*Compact Metal / Alloy with no Risk to Human Health or the Environment.
- \* Summary: tantalum, tantalum (Ta2.5W/Ta10W) additional 2,5/10 % mass fraction tungsten EC no. tantalum: 231-135-5, tungsten: 231-143-9 CAS no. tantalum: 7440-25-7, tungsten: 7440-33-7
- \* Hazardous components: none
- \* Inhalation: no exposure when used as directed. \*Skin contact: wash dust off thoroughly with soap and water. \* Doctor is needed or advisable: consult a physician after prolonged exposure to dust.
- \* Suitable extinguishing media: The product itself is not flammable. \*Adapt extinguishing measures to surroundings.\*Special hazard: increased fire hazard during dust formation. \*Protective equipment: breathing protection in the presence of dust.
- Personnel-related precautionary measures: dust should be suction cleaned directly at source.

  Environmental protection measures: no particular environmental protection measures are required.
- Handling: Avoid dust formation. \*Use suction cleaning with filter if unavoidable.
- \* Storage: no special measures required.
- \* Exposure thresholds: workplace: tantalum 5 mg/m³, tungsten 5 mg/m³ inhalable fraction, mean daily value \*Dust-like emissions: General 5 mg/m³ \*Wastewater emissions: tungsten 5 mg/l \*Workplace exposure: install suction cleaning when working with dust and sublimate and use at least one FFP2 respirator. \*Environmental exposure: install suction cleaning with filter when working with dust formation.
  \* Do not empty into drains.

\* Appearance: solid grey material \*Melting point: 2996°C \*Density: 16,6 g/cm³ at 20°C \*Solubility: insoluble

- in water, acids and bases, soluble only in oxidizing acids in combination with hydrofluoric acid.
- \* Conditions to be avoided: none \*Substances to be avoided: none
- No known toxic effects.
- \* Ecotoxicity: No known ecotoxic effects. \*Mobility: low mobility due to low solubility. \*Persistence and degradability: stable inorganic material. \*Bioaccumulation potential: no data available.
- \* Dispose of residues as metal waste. \*Obey national or regional regulations.
- \* ADR / RID / ADN / IATA (ICAO) / IMDG: not a dangerous good pursuant to international transport regulations.
- \* No labeling required. \*The exposure thresholds given under item 8 pertain to Austrian legal regulations.
- \* Obey national regulations.
- \* Above information corresponds to our current state of knowledge However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
- \* Detailed results of the toxicological and ecotoxicological effects are described in the chemical safety report for REACH registration.

Information about the content

Prepared/Updated:	Heeger Materials Inc.
Released:	Heeger Materials Inc.
Valid from:	12-Jul-2022